

# Straight Built (Bare Blade) Type Textiles Spindle





Products Spindles: HZ-2C, HZ - 3C

#### For Machine:

Reiter, L.R (LMW) LR6, LR9, LR7 machines, Texaco, KTTM, MMC, Mazroli, Zinser, Textool, suessen,

For Process Type: Yarn Industries, cotton Industries, Jute Industries,

#### **Product Description**

- Material: spindle blade: EN 31 alloy (bearing steel), wharves: EN 24 alloy
- Spindle's wharves diameter 25.4 mm and above
- supplies complete set with flange, nut, spindle lock
- manufacture spindle for ring diameter: 2.5 " and 3 "
- we supplied spindle with specified insert as Texpart, SKF, (teraspin), Jaylaxmi.







### **Spindle Application**

- Jaylaxmi reduce vibration up to 0.05 mm / sec
- Jaylaxmi reduce noise level to 75 DBA
- Long life
- We can reduce the weight of spindle top part (new design )
- Short delivery time

#### **Advantages**

- Low noise & Power
- Lift size : up to 250 mm
- High speed up-to 10000 rpm
- Dynamically balanced.
- 5 Stage Quality Checks to ensure exquisite quality system maintenance for superior performance.
- Made to fit your system and give higher and better performance index.

## > Technical Data Sheet

Type of Spindle	Wharves dia. (mm)	LIFT size (mm)	Insert / bolster		Speed- RPM(Mechanical)	Weight in kgs (S.U.P)
Straight built (bare blade) type	25.4 and above	250 and above	Jaylaxmi	HF 3C	4,000 to 7,000	0.400 and above



